

View Online at <https://aerobasegroup.com/nsn/5915-01-326-9840>

**Body Outside Diameter:**

0.600 inches

**Body Height:**

0.370 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+110.0 degrees celsius

**Reference Frequency Per Function:**

173.91 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

2.0 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded stud

**Features Provided:**

Shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.5 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

113.91 megahertz blank and 158.91 megahertz blank and 188.91 megahertz blank and 233.91 megahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

158.91 megahertz blank and 188.91 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 50.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

158.91 megahertz blank and 188.91 megahertz blank

**Unpackaged Unit Weight:**

5.0 grams

**Style Designator:**

Round terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0