
Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-328-8964

Overall Length:
3.300 inches
Overall Height:
2.020 inches
Overall Width:
1.000 inches
Unthreaded Mounting Hole Diameter:
Between 0.126 inches and 0.160 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.300 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.800 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
End Application:
Shoehorn
Operating Current Rating Per Function In Amps:
100.0 blank and 150.0 blank
Full Load Insertion Loss Frequencies In Megahertz:
0.5 and 4.0
Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:
47.0 and 34.0
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Features Provided:
Shock resistant
Functional Terminal Type And Quantity:
3 connector, receptacle input-output
Operating Voltage Rating And Type Per Function:
15.0 volts dc blank and 5.0 volts dc blank
Unpackaged Unit Weight:
7.000 ounces
Style Designator:
Filter connector
Reference Number Differentiating Characteristics:
As differentiated by the source control dwr no.
Shelf Life:
N/a
Unit Of Measure:



Demilitarization:

Yes - demil/mli

Fiig:

A047b0