

View Online at <https://aerobasegroup.com/nsn/5915-01-329-1226>

**Overall Length:**

1.000 inches

**Body Length:**

0.465 inches

**Body Outside Diameter:**

0.087 inches

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**End Application:**

Forrestal class cv, oliver perry class ffg, tarawa class lha, arleigh burke class ddg, whidbey island class lsd, spruance class dd (963), nimitz class cvn, safeguard class ars, ticonderoga class cg (47)

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Operating Current Rating Per Function In Amps:**

15.0 blank

**Maximum Voltage Drop Per Function:**

1.0 volts dc blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 250.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

2.0 and 10.0 and 40.0 and 60.0 and 80.0 and 100.0

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 terminal

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Operating Voltage Rating And Type Per Function:**

100.0 volts dc blank

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Body Surface Treatment:**

Tin

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Specification Data:**

28480-9135-0214 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0