

View Online at <https://aerobasegroup.com/nsn/5915-01-329-1226>

Overall Length:

1.000 inches

Body Length:

0.465 inches

Body Outside Diameter:

0.087 inches

Operating Temperature Range:

-25.0/+85.0 degrees celsius

End Application:

Forrestal class cv, oliver perry class ffg, tarawa class lha, arleigh burke class ddg, whidbey island class lsd, spruance class dd (963), nimitz class cvn, safeguard class ars, ticonderoga class cg (47)

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

15.0 blank

Maximum Voltage Drop Per Function:

1.0 volts dc blank

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 250.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

2.0 and 10.0 and 40.0 and 60.0 and 80.0 and 100.0

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 terminal

Functional Terminal Type And Quantity:

1 pin output 2nd function

Operating Voltage Rating And Type Per Function:

100.0 volts dc blank

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

200.0 volts at sea level

Body Surface Treatment:

Tin

Style Designator:

Round terminal/terminals on opposite surfaces

Specification Data:

28480-9135-0214 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0