

View Online at <https://aerobasegroup.com/nsn/5915-01-329-7114>

Overall Length:

1.970 inches

Overall Height:

1.970 inches

Body Length:

1.160 inches

Body Width:

0.790 inches

Body Height:

1.550 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.575 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

0.00025 2nd radio interference

Maximum Voltage Drop Per Function:

1.2 volts ac 1st radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

0.15 and 0.5 and 1.0 and 5.0 and 10.0 and 30.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

22.0 and 35.0 and 40.0 and 46.0 and 50.0 and 49.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Mounting bracket

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

120.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

2.25 kilovolts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0