## NSN 5915-01-330-6484

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-330-6484 **Overall Height:** 0.735 inches **Body Length:** 1.953 inches **Body Width:** 0.594 inches **Body Height:** 0.485 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.600 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.250 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Reference Frequency Per Function:** 75.0 megahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank **Voltage Standing Wave Ratio Per Function:** 1.65 blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: **Functional Terminal Type And Quantity:** 1 pin output 2nd function **Specified Frequencies Of Discrimination Per Function:** 74.8525 megahertz blank and 74.955 megahertz blank and 75.045 megahertz blank and 75.1475 megahertz blank **Thread Size:** 0.112 inches **Body Material:** 

**Frequency Band Width Per Function:** 

Metal

requestey Bana Watti Fer Fallotton.

74.955 megahertz blank and 75.045 megahertz blank

## NSN 5915-01-330-6484

Band Pass Filter - Page 2 of 2



Discrimination At Specif	icationified Freq	uencies Per Fu	unction In Decibels:
--------------------------	-------------------	----------------	----------------------

3.0 blank and 50.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

74.955 megahertz blank and 75.045 megahertz blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A047b0