NSN 5915-01-330-7202

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-330-7202

| Overall Length: |
|---|
| 1.551 inches |
| Overall Height: |
| 1.312 inches |
| Overall Width: |
| 1.312 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.062 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| End Application: |
| Rdr1400cradar |
| Source Impedance Rating Per Function: |
| 50.0 ohms 4th radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 5th radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 60.0 3rd radio interference |
| Operating Current Rating Per Function In Amps: |
| 75.0 6th radio interference |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance 6th radio interference |
| Maximum Tempurature Rise: |
| 25.0 degrees celsius |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Features Provided: |
| Shock resistant |
| Functional Terminal Type And Quantity: |
| 32 friction w/grounding strap and pin input-output |
| Operating Voltage Rating And Type Per Function: |
| 150.0 volts ac 4th radio interference 4th function and 200.0 volts dc 4th radio interference 4th function |
| Body Material: |
| Aluminum |
| Maximum Dielectric Withstanding Dc Voltage: |

500.0 volts at sea level

NSN 5915-01-330-7202

Radio Frequency Interference Filter - Page 2 of 2



| Body Surface Treatment: |
|---------------------------------|
| Cadmium |
| Special Features: |
| 32 filtered functions |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |
| Style Designator: |
| Filter connector |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A047b0