NSN 5915-01-332-2225

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-332-2225

Overall Height:
1.040 inches
Body Length:
1.310 inches
Body Width:
0.630 inches
Body Height:
0.740 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.000 inches
Vibration Resistance Range In Hertz:
+10.0/+33.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.300 inches
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
End Application:
Receiver-recorder set, meteorological data an/smq-11
Reference Frequency Per Function:
30.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
2.0 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 terminal
Features Provided:
Shock resistant
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
2 pin ground 3rd function
Specified Frequencies Of Discrimination Per Function:
29.75 megahertz blank and 29.95 megahertz blank and 30.05 megahertz blank and 30.25 megahertz blank
Body Material:
Metal

NSN 5915-01-332-2225

Band Pass Filter - Page 2 of 2



Frequency Band Width Per Function:

29.95 megahertz blank and 30.05 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 45.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

29.95 megahertz blank and 30.05 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0