NSN 5915-01-332-2227



Radio Frequency Interference Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5915-01-332-2227 **Overall Length:** 1.541 inches **Overall Height:** 1.020 inches Overall Width: 0.625 inches **Unthreaded Mounting Hole Diameter:** 0.122 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.312 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **End Application:** Tactical air operations module an/tyq-2 (v) 1 **Source Impedance Rating Per Function:** 50.0 ohms 4th radio interference **Load Impedance Per Function:** 50.0 ohms 5th radio interference **Operating Current Rating Per Function In Amps:** 7.5 2nd radio interference **Maximum Voltage Drop Per Function:** 1.0 volts dc 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Full Load Insertion Loss Frequencies In Megahertz:

25.0 and 50.0 and 100.0 and 300.0 and 500.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

10.0 and 15.0 and 20.0 and 40.0 and 50.0 and 55.0

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

15 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

100.0 volts dc 6th radio interference 6th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

250.0 volts at sea level

Body Surface Treatment:

Tin

NSN 5915-01-332-2227

Radio Frequency Interference Filter - Page 2 of 2



Special Features:
Fifteen filtered functions
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Style Designator:
Filter connector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A047b0