

View Online at <https://aerobasegroup.com/nsn/5915-01-332-4489>

Overall Length:

Between 12.000 inches and 12.400 inches

Mounting Slot Width:

0.180 inches

Body Length:

10.800 inches

Body Width:

6.500 inches

Body Height:

2.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.400 inches

Vibration Resistance Range In Hertz:

+10.0/+33.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

6.000 inches

Operating Temperature Range:

-28.0/+65.0 degrees celsius

End Application:

Receiver-recorder set an/smq-11

Reference Frequency Per Function:

137.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

50140

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

50140

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

50.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

6 slot

Features Provided:

Shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

126.00 megahertz blank and 135.00 megahertz blank and 139.00 megahertz blank and 148.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

135.00 megahertz blank and 139.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 50.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

135.0 megahertz blank and 139.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0