

View Online at <https://aerobasegroup.com/nsn/5915-01-332-7433>

**Overall Height:**

Between 0.484 inches and 0.508 inches

**Body Length:**

Between 1.242 inches and 1.250 inches

**Body Width:**

Between 0.592 inches and 0.600 inches

**Body Height:**

Between 0.342 inches and 0.350 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.952 inches and 0.968 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.172 inches and 0.188 inches

**Operating Temperature Range:**

-55.0/+110.0 degrees celsius

**Reference Frequency Per Function:**

173.91 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

6 terminal

**Features Provided:**

Moisture resistant and shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.5 blank

**Functional Terminal Type And Quantity:**

4 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

143.91 megahertz blank and 158.91 megahertz blank and 188.91 megahertz blank and 203.91 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

158.91 megahertz blank and 188.91 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 50.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

158.91 megahertz blank and 188.91 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0