

View Online at <https://aerobasegroup.com/nsn/5915-01-332-9393>

**Overall Length:**

1.650 inches

**Overall Height:**

0.925 inches

**Body Length:**

1.500 inches

**Body Width:**

0.750 inches

**Body Height:**

Between 0.470 inches and 0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.150 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.375 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Reference Frequency Per Function:**

3.0 megahertz blank

**Source Impedance Rating Per Function:**

75.0 ohms blank

**Load Impedance Per Function:**

50.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Output Terminal Manufacturer Code:**

95105

**Output Terminal Identification:**

52-043-0000

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Features Provided:**

Moisture resistant and shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 pin ground 3rd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

100.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 3.00 megahertz blank and 7.68 megahertz blank and 10.68 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 3.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 75.0 blank

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0