

View Online at <https://aerobasegroup.com/nsn/5915-01-332-9394>

Overall Length:

1.800 inches

Overall Height:

1.000 inches

Body Length:

1.600 inches

Body Width:

0.500 inches

Body Height:

0.800 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Reference Frequency Per Function:

1.2 megahertz blank

Source Impedance Rating Per Function:

500.0 ohms blank

Load Impedance Per Function:

5.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.20 megahertz blank and 2.176 megahertz blank and 2.352 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 1.20 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0