NSN 5915-01-332-9394

Low Pass Filter - Page 1 of 2

Overall Length: 1.800 inches Overall Height: 1.000 inches Body Length:



View Online at https://aerobasegroup.com/nsn/5915-01-332-9394

| 1.600 inches |
|---|
| Body Width: |
| 0.500 inches |
| Body Height: |
| 0.800 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.128 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.250 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Operating Tempurature Range: |
| -55.0/+105.0 degrees celsius |
| Reference Frequency Per Function: |
| 1.2 megahertz blank |
| Source Impedance Rating Per Function: |
| 500.0 ohms blank |
| Load Impedance Per Function: |
| 5.0 kilohms blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Features Provided: |
| Moisture resistant and shock resistant |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 3.0 blank |
| Functional Terminal Type And Quantity: |
| 2 pin ground 3rd function |
| Maximum Dielectric Withstanding Ac Rms Voltage: |
| 100.0 volts at sea level |
| Specified Frequencies Of Discrimination Per Function: |
| 1.00 hertz blank and 1.20 megahertz blank and 2.176 megahertz blank and 2.352 megahertz blank |
| Body Material: |
| Metal |
| |

NSN 5915-01-332-9394

Low Pass Filter - Page 2 of 2



Frequency Band Width Per Function:

1.00 hertz blank and 1.20 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0