

View Online at <https://aerobasegroup.com/nsn/5915-01-333-1280>

Overall Height:

Between 0.871 inches and 0.903 inches

Body Length:

Between 1.292 inches and 1.308 inches

Body Width:

Between 0.492 inches and 0.508 inches

Body Height:

Between 0.692 inches and 0.708 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.942 inches and 0.958 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.342 inches and 0.358 inches

Operating Temperature Range:

-55.0/+95.0 degrees celsius

Reference Frequency Per Function:

56.2 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

55.20 megahertz blank and 56.1935 megahertz blank and 56.2065 megahertz blank and 58.20 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

56.1935 megahertz blank and 56.2065 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 65.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0