

View Online at <https://aerobasegroup.com/nsn/5915-01-333-4284>

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

+10.0/+70.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

63.0 1st radio interference

Operating Current Rating Per Function In Amps:

10.0 2nd radio interference

Maximum Voltage Drop Per Function:

5.0 millivolts ac 1st radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Average Power Rating Per Function:

15.0 watts 2nd radio interference

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

8 threaded hole

Features Provided:

Moisture resistant and shock resistant

Functional Terminal Type And Quantity:

2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.164 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

800.0 volts at sea level

Unpackaged Unit Weight:

12.000 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0