

View Online at <https://aerobasegroup.com/nsn/5915-01-334-3738>

**Overall Length:**

6.500 inches

**Overall Height:**

3.000 inches

**Overall Width:**

15.000 inches

**Body Length:**

5.000 inches

**Body Width:**

14.000 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

6.000 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

5.750 inches

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

45.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.15 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 2nd radio interference

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

22.0 and 28.0 and 67.0 and 67.0 and 84.0 and 100.0

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

2 threaded stud input 1st function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

400.0 volts at sea level

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

600.0 volts at sea level

**Special Features:**

Two filtered functions

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0