

View Online at <https://aerobasegroup.com/nsn/5915-01-334-3738>

Overall Length:

6.500 inches

Overall Height:

3.000 inches

Overall Width:

15.000 inches

Body Length:

5.000 inches

Body Width:

14.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

6.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

5.750 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

45.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

22.0 and 28.0 and 67.0 and 67.0 and 84.0 and 100.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

6 unthreaded hole

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

2 threaded stud input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

400.0 volts at sea level

Operating Voltage Rating And Type Per Function:

115.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

600.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0