

View Online at <https://aerobasegroup.com/nsn/5915-01-334-6709>

Overall Length:

0.812 inches

Body Length:

Between 0.432 inches and 0.473 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Average Life Rating In Hours:

1000.0

End Application:

6630-01-082-5483 integrator, comp

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

10.0 blank

Maximum Voltage Drop Per Function:

2.0 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.1 and 1.0 and 10.0 and 100.0 and 1000.0 and 10000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

23.0 and 23.0 and 44.0 and 64.0 and 70.0 and 70.0

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Hermetically sealed

Width Across Flats:

0.250 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 turret input 1st function

Operating Voltage Rating And Type Per Function:

200.0 volts dc blank

Thread Size:

0.216 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Body Surface Treatment:

Tin

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0