

View Online at <https://aerobasegroup.com/nsn/5915-01-334-6710>

**Overall Length:**

0.600 inches

**Body Length:**

0.340 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+500.0 degrees celsius

**Average Life Rating In Hours:**

1000.0

**End Application:**

6630-01-082-5483 integrator, comp

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Operating Current Rating Per Function In Amps:**

10.0 blank

**Maximum Voltage Drop Per Function:**

1.0 volts dc blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.1 and 1.0 and 10.0 and 100.0 and 1000.0 and 10000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

23.0 and 23.0 and 44.0 and 64.0 and 70.0 and 70.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Width Across Flats:**

Between 0.154 inches and 0.159 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Operating Voltage Rating And Type Per Function:**

100.0 volts dc blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

250.0 volts at sea level

**Body Surface Treatment:**

Tin

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0