

View Online at <https://aerobasegroup.com/nsn/5915-01-334-7805>

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 5th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 6th radio interference

**Operating Current Rating Per Function In Amps:**

5.0 3rd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 6th radio interference

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 connector

**Functional Terminal Type And Quantity:**

35 friction w/grounding strap and pin input-output

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 6th radio interference 6th function and 200.0 volts dc 6th radio interference 6th function

**Body Material:**

Aluminum

**Maximum Dielectric Withstanding Dc Voltage:**

10.0 volts at sea level

**Body Surface Treatment:**

Cadmium

**Criticality Code Justification:**

Feat

**Special Features:**

35 filtered functions; unique item differentiated by mounting keyways

**Unpackaged Unit Weight:**

6.000 ounces

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0