

View Online at https://aerobasegroup.com/nsn/5915-01-334-7805

Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference **Power Line Frequency Rating Per Function In Hertz:** 400.0 6th radio interference **Operating Current Rating Per Function In Amps:** 5.0 3rd radio interference **Principal Circuitry Type Per Function:** Inductance-capacitance 6th radio interference Maximum Tempurature Rise: 25.0 degrees celsius **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 1 connector **Functional Terminal Type And Quantity:** 35 friction w/grounding strap and pin input-output **Operating Voltage Rating And Type Per Function:** 120.0 volts ac 6th radio interference 6th function and 200.0 volts dc 6th radio interference 6th function **Body Material:** Aluminum Maximum Dielectric Withstanding Dc Voltage: 10.0 volts at sea level **Body Surface Treatment:** Cadmium **Criticality Code Justification:** Feat **Special Features:** 35 filtered functions; unique item differentiated by mounting keyways **Unpackaged Unit Weight:** 6.000 ounces **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli

NSN 5915-01-334-7805

Radio Frequency Interference Filter - Page 2 of 2

Fiig: A047b0

