

View Online at <https://aerobasegroup.com/nsn/5915-01-336-1764>

**Overall Length:**

0.814 inches

**Body Outside Diameter:**

0.385 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Operating Current Rating Per Function In Amps:**

15.0 blank

**Maximum Voltage Drop Per Function:**

1.0 volts dc blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Maximum Temperature Rise:**

125.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 0.3 and 1.0 and 10.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

4.0 and 14.0 and 21.0 and 31.0 and 50.0 and 70.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Operating Voltage Rating And Type Per Function:**

100.0 volts dc blank

**Thread Size:**

0.250 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

200.0 volts at sea level

**Unpackaged Unit Weight:**

10.000 ounces

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0