

View Online at <https://aerobasegroup.com/nsn/5915-01-336-3287>

Overall Length:

Between 2.750 inches and 3.150 inches

Body Outside Diameter:

0.250 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+71.0 degrees celsius

End Application:

Simulator, airborne jammer an/alt-4 (v)

Reference Frequency Per Function:

12.0 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

50140

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

50140

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

2.0 blank

Average Power Rating Per Function:

2.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Features Provided:

Shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

2.50 gigahertz blank and 3.93 gigahertz blank and 8.07 gigahertz blank and 9.00 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

3.93 gigahertz blank and 8.07 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

3.93 gigahertz blank and 8.07 gigahertz blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0