

View Online at <https://aerobasegroup.com/nsn/5915-01-336-3696>

Overall Height:

0.600 inches

Body Length:

1.500 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.380 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.380 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

624.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.2 blank

Average Power Rating Per Function:

0.05 watts blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

470.00 megahertz blank and 564.00 megahertz blank and 684.00 megahertz blank and 728.00 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

564.00 megahertz blank and 684.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

564.0 megahertz blank and 684.0 megahertz blank

Body Surface Treatment:

Nickel

Unpackaged Unit Weight:

24.0 grams

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0