## NSN 5915-01-336-5430

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-336-5430

Overall Height:
-
0.600 inches
Body Length:
1.750 inches
Body Width:
0.500 inches
Body Height:
0.400 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.630 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.380 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Reference Frequency Per Function:
260.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
1.2 blank
Average Power Rating Per Function:
0.05 watts blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
4.0 blank
Functional Terminal Type And Quantity:
1 pin output 2nd function
Specified Frequencies Of Discrimination Per Function:
208.00 megahertz blank and 234.00 megahertz blank and 286.00 megahertz blank and 312.00 megahertz blank
Thread Size:
0.086 inches
Body Material:
Metal

## NSN 5915-01-336-5430

Band Pass Filter - Page 2 of 2



## **Frequency Band Width Per Function:**

234.00 megahertz blank and 286.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 75.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:** 

234.0 megahertz blank and 286.0 megahertz blank

**Body Surface Treatment:** 

Nickel

**Unpackaged Unit Weight:** 

24.0 grams

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0