

View Online at <https://aerobasegroup.com/nsn/5915-01-336-5433>

Overall Length:

20.000 inches

Body Length:

17.500 inches

Body Width:

4.000 inches

Body Height:

8.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.000 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

3.000 inches

Operating Temperature Range:

-46.0/+71.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Operating Current Rating Per Function In Amps:

200.0 2nd radio interference

Maximum Voltage Drop Per Function:

0.28 volts dc 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

40.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 0.2 and 0.6 and 1.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

3.0 and 20.0 and 40.0 and 60.0 and 90.0 and 90.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

12 threaded stud

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

2 threaded stud input 1st function

Operating Voltage Rating And Type Per Function:

28.0 volts dc 1st radio interference 1st function

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Body Surface Treatment:

Tin

Special Features:

Two filtered functions

Unpackaged Unit Weight:

33.000 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0