

View Online at <https://aerobasegroup.com/nsn/5915-01-336-5437>

Overall Length:

14.430 inches

Mounting Slot Width:

0.281 inches

Body Length:

12.000 inches

Body Width:

8.000 inches

Body Height:

8.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.000 inches

Vibration Resistance Range In Hertz:

+5.0/+200.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

9.500 inches

Operating Temperature Range:

-40.0/+49.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 4th radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 3rd radio interference

Operating Current Rating Per Function In Amps:

200.0 4th radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd radio interference

Maximum Temperature Rise:

40.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.15 and 1.0 and 10.0 and 100.0 and 500.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

60.0 and 80.0 and 80.0 and 80.0 and 80.0 and 80.0

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 slot

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

4 threaded stud output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

230.0 volts at sea level

Operating Voltage Rating And Type Per Function:

115.0 volts ac 4th radio interference 4th function

Body Material:

Metal

Special Features:

Four filtered functions

Unpackaged Unit Weight:

48.000 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0