

View Online at <https://aerobasegroup.com/nsn/5915-01-336-5437>

**Overall Length:**

14.430 inches

**Mounting Slot Width:**

0.281 inches

**Body Length:**

12.000 inches

**Body Width:**

8.000 inches

**Body Height:**

8.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

7.000 inches

**Vibration Resistance Range In Hertz:**

+5.0/+200.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

9.500 inches

**Operating Temperature Range:**

-40.0/+49.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 4th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 3rd radio interference

**Operating Current Rating Per Function In Amps:**

200.0 4th radio interference

**Maximum Voltage Drop Per Function:**

1.15 volts ac 3rd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference

**Maximum Temperature Rise:**

40.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.15 and 1.0 and 10.0 and 100.0 and 500.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

60.0 and 80.0 and 80.0 and 80.0 and 80.0 and 80.0

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 slot

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

4 threaded stud output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

230.0 volts at sea level

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 4th radio interference 4th function

**Body Material:**

Metal

**Special Features:**

Four filtered functions

**Unpackaged Unit Weight:**

48.000 pounds

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0