NSN 5915-01-336-9950

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-336-9950

Overall Length:
4.000 inches
Overall Height:
2.500 inches
Overall Width:
5.500 inches
Mounting Slot Width:
0.220 inches
Body Length:
2.500 inches
Body Width:
4.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.312 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
3.000 inches
Operating Tempurature Range:
-54.0/+65.0 degrees celsius
Average Life Rating In Hours:
1000.0
End Application:
Tactical air operations module an/tyq-2 (v) 1
Source Impedance Rating Per Function:
125.0 ohms 2nd radio interference
Load Impedance Per Function:
125.0 ohms 1st radio interference
Power Line Frequency Rating Per Function In Hertz:
20.0 2nd radio interference
Operating Current Rating Per Function In Amps:
0.1 2nd radio interference
Maximum Voltage Drop Per Function:
0.9 volts ac 2nd radio interference and 0.28 volts dc 2nd radio interference
Principal Circuitry Type Per Function:
Inductance-capacitance 2nd radio interference
Input Terminal Manufacturer Code:
13973
Input Terminal Identification:
Sma-receptacle
Output Terminal Manufacturer Code:
13973

NSN 5915-01-336-9950

Radio Frequency Interference Filter - Page 2 of 2



Output Terminal Identification:
Sma-receptacle
Maximum Tempurature Rise:
25.0 degrees celsius
Full Load Insertion Loss Frequencies In Megahertz:
0.0 and 0.1 and 0.15 and 1.0 and 100.0 and 1000.0
Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:
1.5 and 78.0 and 100.0 and 100.0 and 100.0 and 100.0
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
4 slot
Features Provided:
Fungus resistant and shock resistant
Functional Terminal Type And Quantity:
1 threaded stud ground 3rd function
Operating Voltage Rating And Type Per Function:
90.0 volts ac 2nd radio interference 2nd function and 28.0 volts dc 2nd radio interference 2nd function
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
500.0 volts at sea level
Special Features:
Two filtered functions
Unpackaged Unit Weight:
3.000 pounds
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A047b0