NSN 5915-01-337-5536

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-337-5536

| Overall Length: |
|--|
| 2.850 inches |
| Overall Height: |
| 1.800 inches |
| Body Length: |
| 2.250 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 1.500 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.000 inches |
| Vibration Resistance Range In Hertz: |
| +55.0/+200.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.250 inches |
| Operating Tempurature Range: |
| +0.0/+65.0 degrees celsius |
| Reference Frequency Per Function: |
| 400.0 megahertz blank |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Input Terminal Manufacturer Code: |
| 94990 |
| Input Terminal Identification: |
| Sma-receptacle |
| Output Terminal Manufacturer Code: |
| 94990 |
| Output Terminal Identification: |
| Sma-receptacle |
| Voltage Standing Wave Ratio Per Function: |
| 1.5 blank |
| Average Power Rating Per Function: |
| 25.0 watts blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |

Hermetically sealed

NSN 5915-01-337-5536

Low Pass Filter - Page 2 of 2

A047b0



| Mounting Facility Type And Quantity: |
|---|
| 4 threaded hole |
| Features Provided: |
| Moisture resistant and shock resistant |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 0.7 blank |
| Functional Terminal Type And Quantity: |
| 1 connector, receptacle input 1st function1 connector, receptacle output 2nd function |
| Specified Frequencies Of Discrimination Per Function: |
| 225.00 megahertz blank and 400.00 megahertz blank and 450.00 megahertz blank and 3.20 gigahertz blank |
| Thread Size: |
| 0.086 inches |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 225.00 megahertz blank and 400.00 megahertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 0.7 blank and 40.0 blank |
| Voltage Standing Wave Ratio Frequency Limits Per Function: |
| 225.0 megahertz blank and 400.0 megahertz blank |
| Special Features: |
| Includes power sensor with two d.C. Output terminals and one ground terminal; electrostatic sensitive |
| Style Designator: |
| Rectangular terminal/terminals on two surfaces |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |