

View Online at <https://aerobasegroup.com/nsn/5915-01-338-2032>

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Average Life Rating In Hours:**

500.0

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 5th radio interference

**Operating Current Rating Per Function In Amps:**

5.0 3rd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 6th radio interference

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Moisture resistant and shock resistant

**Functional Terminal Type And Quantity:**

35 friction w/grounding strap and pin input-output

**Operating Voltage Rating And Type Per Function:**

200.0 volts dc 4th radio interference 4th function

**Thread Size:**

0.112 inches

**Body Material:**

Aluminum

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Body Surface Treatment:**

Cadmium

**Criticality Code Justification:**

Feat

**Special Features:**

35 filtered contacts; nuclear hardness critical item

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0