

View Online at <https://aerobasegroup.com/nsn/5915-01-339-2122>

**Overall Length:**

11.000 inches

**Overall Height:**

5.110 inches

**Mounting Slot Width:**

0.203 inches

**Body Length:**

9.000 inches

**Body Width:**

8.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

7.500 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**End Application:**

Radar set an/sps-40c

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 1st radio interference 60.0 2nd radio interference 60.0 3rd radio interference

**Operating Current Rating Per Function In Amps:**

30.0 1st radio interference 30.0 2nd radio interference 30.0 3rd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

5 slot

**Features Provided:**

Mounting bracket

**Functional Terminal Type And Quantity:**

3 tab, solder lug input 1st function 3 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

440.0 volts ac 1st radio interference 1st function 440.0 volts ac 2nd radio interference 2nd function 440.0 volts ac 3rd radio interference 3rd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

800.0 volts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

Includes two channel mounting brackets top and bottom

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0