

View Online at <https://aerobasegroup.com/nsn/5915-01-339-3240>

**Overall Height:**

0.465 inches

**Body Length:**

0.940 inches

**Body Width:**

0.440 inches

**Body Height:**

0.320 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.780 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.280 inches

**Operating Temperature Range:**

-55.0/+110.0 degrees celsius

**Reference Frequency Per Function:**

1.03 gigahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Moisture resistant and shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.5 blank

**Functional Terminal Type And Quantity:**

1 pin input 1st function 1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

960.00 megahertz blank and 1.02 gigahertz blank and 1.04 gigahertz blank and 1.10 gigahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.02 gigahertz blank and 1.04 gigahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.02 gigahertz blank and 1.04 gigahertz blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0