

View Online at <https://aerobasegroup.com/nsn/5915-01-339-3240>

Overall Height:

0.465 inches

Body Length:

0.940 inches

Body Width:

0.440 inches

Body Height:

0.320 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.780 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.280 inches

Operating Temperature Range:

-55.0/+110.0 degrees celsius

Reference Frequency Per Function:

1.03 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Moisture resistant and shock resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

0.5 blank

Functional Terminal Type And Quantity:

1 pin input 1st function 1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

960.00 megahertz blank and 1.02 gigahertz blank and 1.04 gigahertz blank and 1.10 gigahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.02 gigahertz blank and 1.04 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.02 gigahertz blank and 1.04 gigahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0