NSN 5915-01-339-4142

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-339-4142

Overall Length:
7.130 inches
Overall Height:
3.000 inches
Overall Width:
118.250 inches
Body Length:
6.000 inches
Body Width:
8.500 inches
Unthreaded Mounting Hole Diameter:
0.209 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
6.562 inches
Vibration Resistance Range In Hertz:
+5.0/+3000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
4.000 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
End Application:
Mobilegndterm
Source Impedance Rating Per Function:
50.0 ohms 1st radio interference50.0 ohms 2nd radio interference
Load Impedance Per Function:
50.0 ohms 1st radio interference50.0 ohms 2nd radio interference
Power Line Frequency Rating Per Function In Hertz:
60.0 1st radio interference60.0 2nd radio interference
Operating Current Rating Per Function In Amps:
25.0 1st radio interference25.0 2nd radio interference
Maximum Voltage Drop Per Function:
1.8 volts ac 1st radio interference1.8 volts ac 2nd radio interference
Principal Circuitry Type Per Function:
Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference
Input Terminal Manufacturer Code:
96906
Input Terminal Identification:
Ms27468e17f6p
Output Terminal Manufacturer Code:
96906
Output Terminal Identification:

Ms27466e17f6s

NSN 5915-01-339-4142

Radio Frequency Interference Filter - Page 2 of 2



Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 unthreaded hole
Features Provided:
Shock resistant
Functional Terminal Type And Quantity:
1 connector, receptacle input 1st function1 connector, receptacle output 2nd function and 2 threaded stud output 2nd function1 threaded
stud ground 3rd function
Operating Voltage Rating And Type Per Function:
120.0 volts ac 1st radio interference 1st function120.0 volts ac 2nd radio interference 2nd function
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
350.0 volts at sea level
Body Surface Treatment:
Tin
Special Features:
Two filtered functions
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A047b0