

View Online at <https://aerobasegroup.com/nsn/5915-01-340-5765>

Overall Length:

1.620 inches

End Application:

1520-01-298-4532 helicopter, utility

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 1st radio interference 400.0 2nd radio interference 400.0 3rd radio interference 400.0 4th radio interference 400.0 5th radio interference 400.0 6th radio interference

Operating Current Rating Per Function In Amps:

7.5 1st radio interference 7.5 2nd radio interference 7.5 3rd radio interference 7.5 4th radio interference 7.5 5th radio interference 7.5 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

10 terminal

Functional Terminal Type And Quantity:

10 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

120.0 volts ac 1st radio interference 1st function and 200.0 volts dc 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function and 200.0 volts dc 2nd radio interference 2nd function 120.0 volts ac 3rd radio interference 3rd function and 200.0 volts dc 3rd radio interference 3rd function 120.0 volts ac 4th radio interference 4th function and 200.0 volts dc 4th radio interference 4th function 120.0 volts ac 5th radio interference 5th function and 200.0 volts dc 5th radio interference 5th function 120.0 volts ac 6th radio interference 6th function and 200.0 volts dc 6th radio interference 6th function

Body Material:

Aluminum

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Body Surface Treatment:

Cadmium

Special Features:

10 filtered functions

Unpackaged Unit Weight:

0.087 pounds

Style Designator:

Filter connector

Fig:

A047b0