

View Online at <https://aerobasegroup.com/nsn/5915-01-340-8949>

Operating Temperature Range:

+0.0/+70.0 degrees celsius

End Application:

Sm-868/ssq-91

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Operating Current Rating Per Function In Amps:

30.0 1st radio interference 30.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 1st radio interference 1.15 volts dc 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms3402d22-2p

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 2 screw output 2nd function 1 screw ground 3rd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function 115.0 volts dc 2nd radio interference 2nd function

Thread Size:

0.250 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

230.0 volts at sea level

Special Features:

Two filtered functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0