

View Online at <https://aerobasegroup.com/nsn/5915-01-340-8949>

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**End Application:**

Sm-868/ssq-91

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Operating Current Rating Per Function In Amps:**

30.0 1st radio interference 30.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.15 volts ac 1st radio interference 1.15 volts dc 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

**Input Terminal Manufacturer Code:**

96906

**Input Terminal Identification:**

Ms3402d22-2p

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 threaded hole

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 2 screw output 2nd function 1 screw ground 3rd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 1st radio interference 1st function 115.0 volts dc 2nd radio interference 2nd function

**Thread Size:**

0.250 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

230.0 volts at sea level

**Special Features:**

Two filtered functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0