

View Online at <https://aerobasegroup.com/nsn/5915-01-340-9134>

Overall Length:

3.740 inches

Body Length:

2.500 inches

Body Width:

2.000 inches

Body Height:

1.750 inches

Unthreaded Mounting Hole Diameter:

0.180 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.940 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference 3.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

40.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.15 and 1.0 and 5.0 and 10.0 and 30.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

1.0 and 65.0 and 75.0 and 65.0 and 65.0 and 60.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

2 tab, solder lug input 1st function 2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0