

View Online at <https://aerobasegroup.com/nsn/5915-01-340-9963>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 1st radio interference400.0 2nd radio interference400.0 3rd radio interference

Operating Current Rating Per Function In Amps:

30.0 1st radio interference30.0 2nd radio interference30.0 3rd radio interference

Maximum Voltage Drop Per Function:

2.5 volts ac 1st radio interference and 6.0 volts dc 1st radio interference2.5 volts ac 2nd radio interference and 6.0 volts dc 2nd radio interference2.5 volts ac 3rd radio interference and 6.0 volts dc 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference

Maximum Temperature Rise:

40.0 degrees celsius

Inclosure Type:

Encased

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

3 threaded stud input 1st function3 threaded stud output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Operating Voltage Rating And Type Per Function:

250.0 volts ac 1st radio interference 1st function and 600.0 volts dc 1st radio interference 1st function250.0 volts ac 2nd radio interference 2nd function and 600.0 volts dc 2nd radio interference 2nd function250.0 volts ac 3rd radio interference 3rd function and 600.0 volts dc 3rd radio interference 3rd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.2 kilovolts at sea level

Body Surface Treatment:

Tin

Special Features:

Three filtered functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0