

View Online at <https://aerobasegroup.com/nsn/5915-01-341-3235>

Overall Length:

8.000 inches

Mounting Slot Width:

0.203 inches

Body Length:

6.000 inches

Body Width:

6.500 inches

Body Height:

3.000 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

End Application:

An/sps 400 fc

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

30.0 1st radio interference 30.0 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

3 slot 2 threaded bushing

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

2 tab, solder lug input 1st function 2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

Thread Size:

1.125 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

200.0 volts at sea level

Body Surface Treatment:

Tin

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0