

View Online at <https://aerobasegroup.com/nsn/5915-01-341-6886>

Overall Length:

17.250 inches

Overall Height:

8.406 inches

Body Length:

16.000 inches

Body Width:

5.000 inches

Body Height:

6.000 inches

Unthreaded Mounting Hole Diameter:

0.199 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

16.625 inches

Vibration Resistance Range In Hertz:

+5.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

5.626 inches

Operating Temperature Range:

+0.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

End Application:

G202433

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference 60.0 3rd radio interference

Operating Current Rating Per Function In Amps:

25.0 1st radio interference 25.0 2nd radio interference 25.0 3rd radio interference

Maximum Voltage Drop Per Function:

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference 1.2 volts ac 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms3402ds22-22p

Maximum Temperature Rise:

40.0 degrees celsius

Average Power Rating Per Function:

60.0 watts 1st radio interference 60.0 watts 2nd radio interference 60.0 watts 3rd radio interference

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

14 unthreaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 3 threaded stud output 2nd function 1 pin ground 3rd function

Operating Voltage Rating And Type Per Function:

440.0 volts ac 1st radio interference 1st function 440.0 volts ac 2nd radio interference 2nd function 440.0 volts ac 3rd radio interference 3rd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

2.5 kilovolts at sea level

Body Surface Treatment:

Tin

Special Features:

Three filtered functions

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0