

View Online at <https://aerobasegroup.com/nsn/5915-01-341-9547>

**Overall Length:**

5.950 inches

**Overall Height:**

2.570 inches

**Body Length:**

5.650 inches

**Body Width:**

2.060 inches

**Body Height:**

1.820 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

5.150 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.400 inches

**Operating Temperature Range:**

-54.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

30000.0

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

440.0 1st radio interference 440.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

3.5 1st radio interference 3.5 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.15 volts ac 1st radio interference 1.15 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference  
inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

**Maximum Temperature Rise:**

30.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

7 threaded hole

**Features Provided:**

Shock resistant

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 2 tab, solder lug output 2nd function 1 tab, solder lug ground 3rd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 1st radio interference 1st function 115.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1.0 kilovolts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

Two filtered functions

**Unpackaged Unit Weight:**

3.000 pounds

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0