

View Online at <https://aerobasegroup.com/nsn/5915-01-342-0398>

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.990 inches and 4.010 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

440.0 1st radio interference 440.0 2nd radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference 3.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 1st radio interference 1.15 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

30.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 2 tab, solder lug output 2nd function 1 tab, solder lug ground 3rd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function 115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.138 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Body Surface Treatment:

Tin

Special Features:

Two filtered functions

Unpackaged Unit Weight:

1.700 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0