

View Online at <https://aerobasegroup.com/nsn/5915-01-342-0399>

Overall Length:

Between 29.875 inches and 30.125 inches

Body Length:

Between 27.875 inches and 28.125 inches

Body Width:

Between 6.875 inches and 7.125 inches

Body Height:

Between 5.375 inches and 5.675 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 4.940 inches and 5.060 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

30.0 1st radio interference 30.0 2nd radio interference

Maximum Voltage Drop Per Function:

2.5 volts ac 1st radio interference and 0.5 volts dc 1st radio interference 2.5 volts ac 2nd radio interference and 0.5 volts dc 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 slot

Maximum Dielectric Withstanding Ac Rms Voltage:

418.0 volts at sea level

Operating Voltage Rating And Type Per Function:

120.0 volts ac 1st radio interference 1st function and 208.0 volts dc 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function and 208.0 volts dc 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

240.0 volts at sea level

Body Surface Treatment:

Tin

Special Features:

Two filterer functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0