

View Online at <https://aerobasegroup.com/nsn/5915-01-342-0400>

Overall Length:

6.500 inches

Overall Height:

1.942 inches

Body Length:

6.000 inches

Body Width:

2.000 inches

Body Height:

1.380 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Average Life Rating In Hours:

10000.0

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

440.0 1st radio interference 440.0 2nd radio interference

Operating Current Rating Per Function In Amps:

1.5 1st radio interference 1.5 2nd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 1st radio interference 1.15 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

30.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 2 threaded stud output 2nd function 1 threaded stud ground 3rd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function 115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.138 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

1.0 kilovolts at sea level

Special Features:

Two filtered functions

Unpackaged Unit Weight:

1.500 pounds

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0