

View Online at <https://aerobasegroup.com/nsn/5915-01-342-2772>

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 1st radio interference 400.0 2nd radio interference 400.0 3rd radio interference 400.0 4th radio interference 400.0 5th radio interference 400.0 6th radio interference

**Operating Current Rating Per Function In Amps:**

5.0 1st radio interference 5.0 2nd radio interference 5.0 3rd radio interference 5.0 4th radio interference 5.0 5th radio interference 5.0 6th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

**Mounting Facility Screw Thread Series Designator:**

Unef

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Moisture resistant and shock resistant

**Functional Terminal Type And Quantity:**

37 friction w/grounding strap and pin input-output

**Operating Voltage Rating And Type Per Function:**

200.0 volts ac 1st radio interference 1st function 200.0 volts ac 2nd radio interference 2nd function 200.0 volts ac 3rd radio interference 3rd function 200.0 volts ac 4th radio interference 4th function 200.0 volts ac 5th radio interference 5th function 200.0 volts ac 6th radio interference 6th function

**Thread Size:**

1.125 inches

**Body Material:**

Aluminum

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Body Surface Treatment:**

Cadmium

**Shelf Life:**

N/a

**Unit Of Measure:**