

View Online at <https://aerobasegroup.com/nsn/5915-01-342-3382>

**Overall Length:**

2.088 inches

**Overall Width:**

0.600 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

**Operating Current Rating Per Function In Amps:**

5.0 1st radio interference5.0 2nd radio interference5.0 3rd radio interference5.0 4th radio interference5.0 5th radio interference5.0 6th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Functional Terminal Type And Quantity:**

25 friction w/grounding strap and pin input-output

**Operating Voltage Rating And Type Per Function:**

50.0 volts dc 1st radio interference 1st function50.0 volts dc 2nd radio interference 2nd function50.0 volts dc 3rd radio interference 3rd function50.0 volts dc 4th radio interference 4th function50.0 volts dc 5th radio interference 5th function50.0 volts dc 6th radio interference 6th function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

150.0 volts at sea level

**Special Features:**

25 filtered functions

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Filter connector

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fiig:**

A047b0