NSN 5915-01-342-3383

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-342-3383

| Overall Length: |
|--|
| 6.178 inches |
| Body Length: |
| 5.250 inches |
| Body Width: |
| 2.500 inches |
| Body Height: |
| 1.250 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.188 inches |
| End Application: |
| 5865-01-303-0305 data processor |
| Source Impedance Rating Per Function: |
| 300.0 ohms 1st radio interference300.0 ohms 2nd radio interference |
| Load Impedance Per Function: |
| 600.0 ohms 1st radio interference600.0 ohms 2nd radio interference |
| Operating Current Rating Per Function In Amps: |
| 0.2 1st radio interference0.2 2nd radio interference |
| Maximum Voltage Drop Per Function: |
| 1.5 volts dc 1st radio interference1.5 volts dc 2nd radio interference |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 2 threaded bushing1 unthreaded hole |
| Functional Terminal Type And Quantity: |
| 2 tab, solder lug input 1st function2 tab, solder lug output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 300.0 volts dc 1st radio interference 1st function300.0 volts dc 2nd radio interference 2nd function |
| Thread Size: |
| 0.438 inches |
| Body Material: |
| Metal |
| Special Features: |
| Two filtered functions |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |
| Shelf Life: |

N/a

NSN 5915-01-342-3383

Radio Frequency Interference Filter - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0